

VISSONIC

Professional Audio Video Manufacturer

CLEACON V2

Wi-Fi Wireless Conference System

PRODUCT DATASHEET



VISSONIC ELECTRONICS LTD.

Think Solutions

New CLEACON V2 Generation 5GHz Wi-Fi Wireless Conference System, with High Tech in DSP unique Sound Processing

CLEACON V2 5GHz Wi-Fi Wireless Conference System

Standard Wi-Fi Communication

Our CLEACON wireless conference system is an innovative system based on standard Wi-Fi technology and self-adjustment technology. The system work in the 2.4Hz and 5GHz band and get the 44 channels for communication to coexist with other Wi-Fi network. The unique self-adaptive technology is strong anti-interference ability ensure the system interference-free and highly flexible for different application. The standard Wi-Fi Technology make the system can work in around the world and no ISM limit.

Ease of Use

The system is no additional cabling and testing and run under the 25-meter radius of Wi-Fi signal which is full 360-degree coverage. All microphone units automatically identify the access point and communicate with WPA2 secure connection to ensure the conferencing safety.

Compact yet versatile design

The product design reflects the elegant, yet compact and easy to use features. Conference unit features a graphical interface operating area, including lighting reminder, anyone can get started quickly. Easy to install, user-friendly to use, and is designed to ensure higher productive meetings.

Excellent legibility sound

Advanced voice processing technology, with the unique design of the microphone head, this unit can be accurate pickup and restore the human voice through a high-quality built-in speakers or an external PA system, original AUDIO-LINK digital ring network technology, Automatic Gain Control Volume(AGC) / automatic frequency control(AFC) technology help reach higher volume without triggering the howling effect, ensures clear sound to every person in the room.

High tech intelligence platform

Timing function, overtime speaking reminder, voting results multi-platform synchronization, network control and meeting management, conference Smart reservation, worldwide firmware real-time updates, the integration of IT technologies ensures smart conferencing platform, the CLEACON is one of them.

VIS-DCP2000-W

Full Digital Networked DSP Conference Processor



Features

- The unique AUDIO-LINK digital ring network technology achieve full-digital signal transmission and processing
- One CAT5e cable to transmit up 64 channels audio and other signals.
- All microphone units support audio, ID independent output. Working with voice recognition system to achieve voice role separation.
- High-fidelity sound quality by lossless audio transmission technology, 48K audio sampling rate and 20Hz ~ 20KHz frequency response
- A single conference controller can realize the independent control and merging of 4 conference rooms, can handle the cascade of multiple conference controllers to realize the merging and separation of larger conference rooms (Optional).
- "Hand-in-Hand-Loop-Network" connection makes the system always working perfectly no matter changing discussion unit or having any malfunctioned units
- The sensitivity of the unit microphone and 8 segment equalizer EQ adjusted independently.
- Conference controller can output 16 segment equalized EQ to achieve sound field adjustment; pressure limit, which can recognize the noise gate passed by human voice. AGC automatic volume gain control; AFC automatic feedback suppression and auto-mix technology.
- Sound output by separated zones function, each zone is automatically adjusted according to the volume of the position of the microphone, achieve longer distances pickup without whistle.
- Echo cancellation, remote two-way real-time call with another conference controller or another third-party video conferencing terminal.
- USB recording, controller monitor, advanced noise cancellation technology to realize clearer recording.
- System date, time management, and support count-down speech.
- Optional DANTE output module with other DANTE equipment used.
- Can drive 2x120W POE speaker, through extension main unit, support up to 16 POE speakers.

Functions

- Compliance with IEC 60914, GBT 15381-94
- Connect with VIS-EXM full-digital extension main unit, it can expand to 5200 discussion units
- "Hand-in-Hand-Loop-Network" connection and the system assigned to each unit independently ID to avoid ID conflict.

Technical Parameters

Power 100V / 240V AC

Static power consumption 12W

Maximum power consumption 150W

Frequency Response 20Hz ~ 20KHz

Noise ratio (S / N) >96dBA

Total harmonic distortion <0.05%

Channel Crosstalk > 85dB

Dynamic range >94dB

RS-232 control: 1×9-pole Sub-D female socket 1×9-pole Sub-D male socket

Ethernet control: RJ45 connected to PC

Mounting: 19" standard rack

Dimensions (mm) 483L x 260W x43.6H

Weight: 3kg

Black color

Max. audio inputs

LINE IN 1: +10dBu

LINE IN 2: +10dBu

Max. audio outputs

LINE OUT 1: +12dBu BAL.

LINE OUT 2: +12dBu BAL.

LINE OUT 3: +12dBu BAL.

LINE OUT 4: +12dBu BAL.

Transmission technology: WIFI 802.1n

Encryption technology: WPA2-PSK AES

Working frequency: 5.2-5.8 GHZ

Output impedance: >1kΩ

PC communication method: TCP/IP

Camera control method: RS-232/UDP

Network Interface: RJ45

Display: LCD1602

Limit on the number of speakers: 1/2/4, max in 6 persons

Camera Tracking Protocol: PELCO-P/PELCO-D/VISCA

Operating temperature: 0 ~ 45°C

Storage temperature: 20 ~ 50°C

Item Model for Order

VIS-DCP2000-W..... Full digital network DSP conference processor

CLEACON V2 Series VIS-MAW-T

WiFi Wireless Touch Screen Unit



Features

- 4.3-inch capacitive color touch screen with stylish and low-profile design
- Built-in NFC card reader for quick identification of participants
- All-in-one touch screen conference unit can be configured into one chairman unit, delegate unit, VIP unit or dual delegate unit according to the different needs of each meeting
- The integration of 5G WiFi wireless and wired network, dual connection to communicate makes the meetings be not interrupted
- Three charging methods: replaceable battery power supply, microphone base charging, wired POE network charging. The battery intelligent visual management is carried out in three ways: unit display screen, web server and PC software
- Wireless communication, setting up all system in few minutes to be ready for using, and put them away in short time as well
- Detachable battery pack is easy to replace and charge. The battery can provide 20 hours of runtime after it is fully charged
- Internal high-fidelity loudspeaker
- Pluggable microphone and long-range sound pickup ability, support different length of microphone.
- Head-set interface in both sides with volume adjust
- Line-in interface which allows microphone or other line-in device like cell phone, laptop to pass audio through to perform teleconference
- Full-digital signal transmission and processing, completely avoid the RF interference from cell phone or similar devices.
- The unit showing time/date on the screen. Timer on display to set certain time for each delegate to speak, will

remind user or close the MIC automatically.

- Easily expand functions by setting software modules

Functions

- Compliance with IEC 60914, GBT 15381-94
- Standard Wi-Fi technology is compatible with other Wi-Fi networks, support 2.4GHz and 5GHz on all channels.
- Full-digital transmission and processing technology in uncompressed audio, professional microphone to achieve perfect sound quality at 20Hz ~ 20KHz;
- 128 bits digital encryption technology, with WAP2 secure connection, MAC address filtering, SSID-hiding to prevent wiretapping and unauthorized access from delegate unit
- One AP can work with more than 40 wireless units, and more units can be connected by extension APs
- 6 wireless units can be activated at the same time by the users
- Support more AP working together to increasing the Wi-Fi coverage range for wireless MIC units working in a large conference room or multi-rooms
- With our HD PTZ camera and video matrix switcher, using RS485 or RS232 protocol to send the PELCO/VISCA protocol to realize camera auto-tracking function
- Precise cardioid directional microphone capsule with anti-wind microphone foam, with two-color LED indicator
- Button for MIC ON/OFF, Priority & Apply Answer button for chairman unit
- Built-in high-fidelity speakers, it automatically mutes to prevent howling when press MIC ON
- Head-set interface in both sides with volume adjustment.
- AGC (Automatic Gain Control)/AFC (Adaptive Feedback Cancellation)/ANC (Active Noise Cancellation)/Mix (Auto-Mix) technology
- Build-in functions for intercom
- Contains five optional function modules:
 - Voting: three-button / two-button voting
 - NFC identification: Sign in with NFC card to accurately identify user information.
 - Simultaneous interpretation channel: There are 2 language channel selectors and each selector has 64 languages independent selection
 - Dual users: Support two participants sharing one unit to achieve camera tracking at two locations; enabling two delegates to vote on one unit
- Without using PC software, our conference controller still owns following settings:
 - Limit on the number of speaking persons: By Setting the number of active units at the same time (Number is 1/2/4/6/ units)
 - Discussion modes:
"OPEN" Free for all, limited by the active units setting by controller, "OVERRIDE" First in First out, "VOICE" Can activate MIC by detecting sound without press button, "APPLY" To apply then to speak
- The unit showing real time on the screen, and count-down timer for speaking person.
- Detachable battery pack is easy to replace and charge. The battery can provide 20 hours of runtime after it is fully charged. Power-saving technology enables the microphone to be continuously used for 20 hours and standby for 35 hours.
- Combined with camera and camera tracking controller, it has an automatic camera tracking function.

- Built-in MCU, support wireless upgrade of all units.
- With voice control function, you can adjust the sensitivity of voice control, intelligently turn on the microphone and set the off time.
- Added Type-C interface and side charging contacts for mobile device charging.

Control & Indicators

Microphone with two-color LED ring, red indicates speaking status, green indicates request to speak.

4.3-inch capacitive touch display

Indicator for Volume adjustment

Indicator for MIC ON/OFF

Chairman unit with priority button and consent button for the delegates

Power ON/OFF button is hiding on the left side

Interfaces

Pluggable gooseneck microphone base

2x 3.5mm stereo headphone jack

1x 3.5mm stereo input jack

2x RJ45 connectors

Contact for battery pack

DC Connector for power adaptor

Technical Parameters

Screen size :109.22 mm (4.3 inches)

Resolution: 800x480

Screen type: Capacitive and color multi-touch

Contactless NFC cards in following standards: ISO / IEC14443 Type A

Connection method: CAT5 / CAT6 cable + WiFi wireless + buckle

Sound Pickup: heart type capacitance

Electrical parameters

Power: 48V DC

Power saving mode consumption: 1.4W

Maximum power consumption: 3.8W(connection with wireless and wired together)

Frequency response :20~20000Hz

THD at rated level <0.1%

Dynamic range> 90 dB

S / N ratio≥96dB

THD at rated level <0.1%

Audio input

Nominal microphone input 80 dB SPL in accordance with IEC60914

Maximum sound pressure 125dB (THD <3%), in line with IEC60914

Sensitivity: -46 dBV / Pa

Page 9

Audio output

Headphone load: 16Ω

Headphone volume: 10mW

Headphone jack: 3.5mm stereo

Input impedance: 2kΩ

Mechanical parameter

Installation: desktop

Dimensions (mm, without microphone): 217.5L × 138.5W × 69H

Color: Black

Main material: ABS

Weight (without microphone): 1.0 KG

Environmental parameters

Operating temperature 5 °C to +55 °C

Relative humidity <90%

Item Model for Order

VIS-MAW-T.....WiFi wireless touchscreen unit, battery and microphone are not included

VIS-WBTY2.....Battery pack for each unit,7.2VDC,5000mA

VIS-WBTY2-H.....Battery pack for each unit,7.2VDC,6500mA

VIS-WCH2.....Charger for battery

VIS-M220.....Pluggable Gooseneck Microphone 220mm, unique design

VIS-M330.....330mm Microphone, with anti-wind foam cover

VIS-M410.....410mm Microphone, with anti-wind foam cover

VIS-M485.....485mm Microphone, with anti-wind foam cover

VIS-M600.....600mm Microphone, with anti-wind foam cover

Optional function license

VIS-ALGE Dual 64-channel selector software module

VIS-AVOTE Vote software module

VIS-AIDEN NFC identification software module

VIS-ADUAL Dual user software module

VIS-ICARD

Contactless IC card



Features

- Proven, Reliable Technology - Offers extremely consistent read range
- Fast Processing and Data Communication
- True Credit Card Thickness

Technical Parameters

Dimensions: 2.125 x 3.375x .03" (5.4 x 8.57 x 0.076 cm)

Weight: 6g

Typical Maximum Read Range: Up to 4" (10cm)

Operating Frequency: 13.56MHz

RF Interface: ISO/IEC 14443A/MIFARE, Parts 1-3

Transaction Time: < 100ms

Baud Rate: 106 kbps

Data Retention: 10 years min.

VIS-ALGE/VIS-AVOTE/VIS-AIDEN/VIS-ADUAL

Software modules for WiFi Wireless Touch Screen Unit



Features

- VIS-ALGE: License active to realize new feature for Dual language selector
- VIS-AVOTE: License active to realize new feature for voting function
- VIS-AIDEN: License active to realize new feature for IC card identification
- VIS-ADUAL: License active to realize new feature for dual user

Functions

- VIS-ALGE for simultaneous interpretation channel: There are 2 language channel selectors and each selector has 64 languages independent selection
- VIS-AVOTE for voting: Three-button / two-button voting
- VIS-AIDEN for RFID card identification: Sign in or voting with RFID card to accurately identify user information
- VIS-ADUAL for dual user: Two participants share one wireless touch screen unit to achieve camera tracking at two locations. It also enables two delegates to vote on one unit

Item Model for Order

VIS-ALGE Dual 64-channel selector software module
VIS-AVOTE Vote software module
VIS-AIDEN NFC identification software module
VIS-ADUAL Dual user software module

VIS-AP4C

2.4GHz/5GHz Conference Access Point



Features

- Connect with the Wi-fi conference processor VIS-DCP2000-W, or with the switch to extend more conference AP in the same system.
- Typical coverage range 30m
- Each AP can connect up to 50 conference units.
- Install on ceiling, wall or with stand rack mount
- 128 bits AES digital encryption technology, with WAP2 secure connection, MAC address filtering, SSID-hiding to prevent wiretapping and unauthorized access from delegate unit

Functions

- LED indicator for signal/power
- 5GHz dual band communication
- LAN support POE power supply
- RJ45 for LAN connection

Technical Parameters

RF	
WLAN Standard	IEEE802.11ac, IEEE802.11a, IEEE802.11g, IEEE802.11b
RF Frequency Bands	2.4GHz ISM / 5GHz UNII
Max Transmission Power	27dBm
Antenna Type	Four built-in 5dBi antennas
POWER	
Supply Type	Power Over Ethernet, 802.3at, DC 12V 1.5A
Supply Voltage(at Power Consumption)	≤13W

VIS-M600/VIS-M485/VIS-M410/VIS-M330/VIS-M220

Pluggable Gooseneck Microphone



Features

- Precise directional microphone head with Mini design
- Two color LED ring indicator
- anti-wind microphone foam cover
- Strong audio collection ability to work with different length of microphone

Functions

- Two-color LED indicator on microphone, red for speaking, green means need acceptance from chairman to speak
- Screw lock socket to connect removable microphone

Technical Parameters

Item	VIS-M600	VIS-M485	VIS-M410	VIS-M330	VIS-M220
Directivity	Cardioid				
Sensitivity	-46dBV/Pa				
Frequency response	30Hz~20KHz				
Equivalent noise	20dBA (SPL)				
Signal-To-Noise Ratio Ref	≥96dB				
Microphone Type	Condenser				
Maximum SPL (1 kHz at 1% THD, 1 kΩ load)	125dB (THD<3%)				
Conference unit connection	Mini 6 pin.				
Input impedance	2 kΩ				

Working temperature	0~45°C				
Storage temperature	-20~50°C				
Weight	80g	80g	60g	60g	60g
Length	600mm	485mm	410mm	330mm	220mm
Color	black				

Item Model for Order

- VIS-M220.....Pluggable Gooseneck Microphone 220mm, unique design
- VIS-M330.....330mm Microphone, with anti-wind foam cover
- VIS-M410.....410mm Microphone, with anti-wind foam cover
- VIS-M485.....485mm Microphone, with anti-wind foam cover
- VIS-M600.....600mm Microphone, with anti-wind foam cover

About VISSONIC Electronics Limited

Our mission is to develop and manufacture the most comprehensive and innovative audio visual products for our clients. We provide the best performance/price ratio products because it could give you satisfaction just from the time you use them, we believe the good design with cutting edge technology on products will provide value to all our partners and end users. Listen to your demands, we fulfill it.



4/F, Building 6, No. 50 Nanxiang 1st Road, Huangpu district, Guangzhou, China

• Tel: +86-020-82515140 • E-mail: info@vissonic.com
 @2022 VISSONIC Electronics Ltd. all rights reserved.